


»» Features



- Compact size and low 5mm profile.
- Low power consumption (140mW for single-side stable, 100 to 300mW for latching type).
- Low thermo electromotive force.
- Low magnetic interference enables high-density mounting.
- Single-and double-winding latching types also available.
- UL and CSA approval.

»» Type List

Terminal style	Contact form	Relay function	Terminal shape	Enclosure style
				Plastics sealed
PCB terminal	2C (DPDT)	Single-side stable	PCB terminal	702-2C-S
		Single-winding latching		702U-2C-S
		Double-winding latching		702K-2C-S
		Single-side stable	Surface mount terminal	702F-2C-S-TR

»» Ordering Information

702 U F - 2C - S - TR
1 2 3 4 5 6

- | | | | |
|----------|-----------------------------|----------|-----------------------------|
| 1. 702 | -- Basic series designation | 4. 2C | -- Double pole double throw |
| 2. Blank | -- Single-side stable | 5. S | -- Plastics sealed |
| U | -- Single-winding latching | U | -- Ultrasonically cleanable |
| K | -- Double-winding latching | | |
| 3. Blank | -- PCB terminal | 6. Blank | -- Standard type |
| F | -- Surface mount terminal | TR | -- Tape packing |

»» Contact Rating

Rated load (resistive load)	0.5A at 125VAC, 1A at 30VDC
Contact material	Ag + Au-clad
Max. continuous current	1A
Maximum switching voltage	125VAC, 110VDC
Maximum switching capacity	62.5VA, 33W
Min. permissible load	0.01µA at 10mVDC

Note : P level: $\lambda_{60} = 0.1 \times 10^{-6}$ / operation

702

»» Coil Rating (DC)

◆ Single-side stable

Rated voltage (V)	Rated current (mA)	Coil resistance (Ω)	Max. continuous voltage at 23 °C	Pick up voltage(Max) at 23 °C	Drop out voltage(Min) at 23 °C	Power consumption at rated voltage
3	46.7	64.3				
5	28.1	178	200 % of rated voltage	75 % of rated voltage	10 % of rated voltage	approx. 0.14W
6	23.3	257				
9	15.5	579				
12	11.7	1028				
24	8.3	2880	170 % of rated voltage			approx. 0.2W

◆ Single-winding latching

Rated voltage (V)	Rated current (mA)	Coil resistance (Ω)	Max. continuous voltage at 23 °C	Pick up voltage(Max) at 23 °C	Drop out voltage(Min) at 23 °C	Power consumption at rated voltage
3	33.3	90				
5	20	250				
6	16.7	360	180 % of rated voltage	75 % of rated voltage	75 % of rated voltage	approx. 0.1W
9	11.1	810				
12	8.3	1440				
24	6.25	3840				approx. 0.15W

◆ Double-winding latching

Rated voltage (V)	Rated current (mA)	Coil resistance (Ω)	Max. continuous voltage at 23 °C	Pick up voltage(Max) at 23 °C	Drop out voltage(Min) at 23 °C	Power consumption at rated voltage
3	66.7	45				
5	40	125	160 % of rated voltage	75 % of rated voltage	75 % of rated voltage	approx. 0.2W
6	33.3	180				
9	22.2	405				
12	16.7	720				
24	12.5	1920	130 % of rated voltage			approx. 0.3W

» Specification

Contact resistance ⁽¹⁾	100 mΩ Max.	
Operate time ⁽¹⁾	single-side stable type	: 3 ms Max.
	latching type	: 3 ms Max.
Release time ⁽¹⁾	single-side stable type	: 2 ms Max.
	latching type	: 3 ms Max.
Bounce time	operate	: approx 0.5ms
	release	: approx 0.5ms
	set/reset	: approx 0.5ms
Min. set/reset signal width	latching type : 5 ms min.	
Insulation resistance ⁽¹⁾	1000 MΩ Min. (DC 500V)	
	Between set and reset coil : 100 MΩ (DC 125V)	
Dielectric strength ⁽¹⁾	Between coil and contacts : AC 1000V, 50/60Hz 1 min.	
	Between contact of different polarity : AC 1000V, 50/60Hz 1 min.	
	Between contact of same polarity : AC 750V, 50/60Hz 1 min.	
	Between set and reset coil : AC 125V, 50/60Hz 1 min. (double-winding latching)	
Surge withstand voltage	Between contact of same polarity : AC 1500V (10X160 μs) (conforms to FCC part 68)	
Vibration resistance	Operating extremes	10~55Hz , double amplitude 5 mm
	Damage limits	10~55Hz , double amplitude 3 mm
Shock resistance	Operating extremes	500 m/s ²
	Damage limits	1000 m/s ²
Life expectancy	Mechanical	100,000,000 operations (frequency 36,000 operations/hr)
	Electrical	200,000 operations (frequency 1,800 operations/hr)
Operating ambient temperature	-40 ~ +70 °C (no freezing)	
Weight	Approx. 1.5 g	

Note : (1) initial value

» Safety Approval

Certified	UL	CSA
File No.	E74321	218083



» Safety Approval Rating

UL	CSA
2A 30VDC	2A 30VDC
0.3A 110VDC	0.3A 110VDC
0.5A 125VAC	0.5A 125VAC



702

»» Outline Dimensions

◆702




◆702F




»» Wiring Diagram

BOTTOM VIEW


◆702




◆702U



◆702K




◆702F




»» PC Board Layout

BOTTOM VIEW












◆702



◆702F





»» Engineering Data



702

Shock malfunction

Type:702



Conditions:


Shock is applied in +X, +Y, and +Z directions three times each with and without energizing the Relays to check the number of contact malfunctions.

Rating: 500m/s^2

Electrical life expectancy

(with must operate and must release voltage)


Type:702



Electrical life expectancy

(contact resistance)


Type:702



Contact reliability test


Type:702

Test conditions:
resistive load $10\mu\text{A}/10\text{mVDC}$




External magnetic interference (average value)

Type:702K




External magnetic interference (average value)

Type:702K




External magnetic interference (average value)

Type:702K



Must operate and must release time distribution

Type:702



Must operate and must release bounce time distribution

Type:702

